

Safety Data Sheet

115-3302

CircuitMedic, 22 Parkridge Road, Haverhill, MA 01835 USA
Phone: 978-373-1600 | Website: <http://www.circuitmedic.com>

Revision Date: Jul 13, 2018

CircuitMedic disclaims all liability associated with the use of this information.

Section 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1. Product Identifier

Product Name: Circuit Bond - Resin

Product Number: 115-3302

1.2 Relevant identified uses of the substance or mixture and uses advised against

This is a general purpose adhesive that is packaged in a two-part plastic package. The components are mixed just prior to use. There are no identified uses advised against.

The components include:

115-3302 Circuit Bond - Resin

http://www.circuitmedic.com/msds/msds_circuit_bond_resin.html

115-3302 Circuit Bond - Hardener

http://www.circuitmedic.com/msds/msds_circuit_bond_hardener.html

1.3 Details of the supplier of the safety data sheet

CircuitMedic
22 Parkridge Road, Haverhill, MA 01835 USA
PHONE: 978-373-1600, FAX: 978-372-5700

1.4 Emergency telephone number

For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
Within USA and Canada: 1-800-424-9300 CCN4877
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

Section 2. HAZARD IDENTIFICATION

2.1 Classification of the substance or mixture

Classification of the chemical in accordance with CFR 1910.1200(d)(f):
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830

2.2 Label Elements

Hazard pictograms:



Signal Words:

DANGER

GHS Class:

Carcinogenicity, category 2
 Germ cell mutagenicity, category 2
 Eye Irritation, category 2
 Skin Irritation, category 2
 Skin Sensitization, category 1
 Specific Target Organ Toxicity - STOT, Single Exposure SE. Category 3 (Respiratory tract irritation).
 Hazardous to the aquatic environment, long-term, chronic, category 2

Hazard

Statements:

H351 - Suspected of causing cancer.
 H341 - Suspected of causing genetic defects.
 H319 - Causes serious eye irritation.
 H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H335 - May cause respiratory irritation.
 H411 - Toxic to aquatic life with long lasting effects.

Precautionary

Statements:

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 - Wash hands thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
 P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 - IF exposed or concerned: Get medical advice/attention.
 P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P391 - Collect spillage.
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P405 - Store locked up.
 P501 - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

2.3 Other Hazards

Hazards not otherwise classified that have been identified during the classification process: None known.

Section 3. COMPOSITION, INFORMATION OR INGREDIENTS

3.1. Substance

Not applicable

3.2 Mixtures

Chemical/Ingredient Name	CAS Number	Ingredient Percent	EC Number	Comments
N-butyl Glycidyl Ether	2426-08-6	10 - 15	219-376-4	-
Bisphenol A/epiclorohydrin Resin	25068-38-6	80 - 90	500-033-5	-

Section 4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.

Skin Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3 Indication of any immediate medical attention and special treatment needed

No additional information.

Section 5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.

Unsuitable Media: None.

5.2 Special hazards arising from the substance or mixture

Hazardous Combustion Byproducts: Oxides of carbon, aldehydes, amines, aniline, acids and other organic substances may be formed during combustion. The chemical nature and quantity of decomposition by-products will vary widely depending on the conditions of combustion.

Unusual Fire Sealed containers at elevated temperatures may rupture explosively and spread fire due to

Hazards: polymerization.

5.3 Advice for firefighters

Fire Fighting Instructions: Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA Health: 2

NFPA Fire: 1

NFPA 1

Reactivity:

Section 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personnel Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper personal protective equipment as listed in Section 8.

6.2 Environmental precautions

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

6.3 Methods and material for containment and cleaning up

Methods for Containment: For small spills, activate available exhaust ventilation equipment in the immediate spill area. Wipe up or absorb spilled material with paper towels or other absorbent material. For large spills, dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters.

Methods for Cleanup: For small spills, wash area with soapy water to remove residue. Collect absorbed material and water rinses in appropriate containers. Dispose of in accordance with Federal, State and local regulations. For large spills, recover spilled material on adsorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed thoroughly wet vacuum the area. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Do not flush to sewer.

Other Spill Precautions: Spill response operations must be conducted in accordance with the provisions of OSHA 29 CFR 1910.120. Review the entire SDS before proceeding with spill response.

6.4 Reference to other sections

Use proper personal protective equipment as listed in Section 8.

Section 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist. Avoid contact with eyes, skin, or clothing. Avoid prolonged or repeated contact with skin. Keep container tightly closed when not in use.

Special Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10)

Handling: during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.

Hygiene Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using restroom

Practices: facilities. Promptly remove contaminated clothing and launder thoroughly before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use. Do not reuse empty containers. Keep out of the reach of children.

7.3. Specific end use(s)

No additional information.

Section 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 Control parameters

Exposure Guidelines

N-butyl Glycidyl Ether:

ACGIH: Sensitizer, Skin: Sensitizer, Skin

OSHA: PEL-TWA: 50 ppm

8.2 Exposure controls

Appropriate engineering controls

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Individual protection measures

Eye Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.

Skin Protection: Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant the use of respirators.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Hygiene Practices: Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using restroom facilities. Promptly remove contaminated clothing and launder thoroughly before reuse.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical State:	Liquid.
Color:	Clear amber
Odor:	Not determined.
pH:	Not determined.
Melting Temperature:	Not determined.
Boiling Temperature:	Not determined.
Flash Point:	164 °F
Flash Point Method:	Not determined.
Ignition Temperature:	Not determined.
Lower Flammable Limit:	Not determined.
Upper Flammable Limit:	Not determined.
Vapor Pressure:	Not determined.
Vapor Density:	Not determined.
Solubility:	Slightly soluble.
Specific Gravity:	(Ref: water = 1).
Evaporation Rate:	Not determined.
VOC Content:	Not determined.
Viscosity:	Not determined.
Odor Threshold:	Not determined.

9.2 Other information

None available.

Section 10. STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity: Stable under normal handling and storage conditions.

10.2 Chemical Stability

Chemical Stability: Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

Hazardous Polymerization: It will not vigorously polymerize, decompose, condense or not become self-reactive under conditions of shocks, pressure, or temperature. Uncontrolled mixing with resins may cause hazardous polymerization.

10.4 Conditions To Avoid

Conditions To Avoid: Contact with acidic, basic, or oxidizing materials. Exposure to open flame or uncontrolled heat, uncontrolled mixing or exposure to incompatible substances. Avoid storage in open containers.

10.5 Incompatible Materials

Incompatible Materials: Acidic, basic or oxidizing materials.

10.6 Hazardous decomposition products

None known.

Section 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Bisphenol A/epichlorohydrin Resin:

Eye Administration into the eye - Rabbit Standard Draize test: 100 mg [Mild]

Toxicity: Administration into the eye - Rabbit Standard Draize test: 20 mg/24H [Moderate]
Administration into the eye - Rabbit Standard Draize test: 5 mg/24H [Severe] (RTECS)

Skin Toxicity: Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: >20 mL/kg [Details of toxic effects not reported other than lethal dose value]

Administration onto the skin - Rat LD50 - Lethal dose, 50 percent kill: >1200 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

Ingestion Toxicity: Oral - Rat LD50 - Lethal dose, 50 percent kill: 10700 uL/kg [Details of toxic effects not reported other than lethal dose value]

Oral - Rat LD50 - Lethal dose, 50 percent kill: 13600 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic - Weight loss or decreased weight gain]

Oral - Rat LD50 - Lethal dose, 50 percent kill: 13.6 gm/kg [Details of toxic effects not reported other than lethal dose value]

Oral - Rat LD50 - Lethal dose, 50 percent kill: 11.4 gm/kg [Details of toxic effects not reported other than lethal dose value]

Oral - Rat LD50 - Lethal dose, 50 percent kill: 30 gm/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic - Weight loss or decreased weight gain]

Oral - Rat LD50 - Lethal dose, 50 percent kill: 30 gm/kg [Details of toxic effects not reported other than lethal dose value]

Oral - Rat LD50 - Lethal dose, 50 percent kill: >1 gm/kg [Details of toxic effects not reported other than lethal dose value]

Oral - Rat LD50 - Lethal dose, 50 percent kill: 11400 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic - Weight loss or decreased weight gain] (RTECS)

N-butyl Glycidyl Ether:

Eye Administration into the eye - Rabbit Standard Draize test: 91 mg [Mild]

Toxicity: Administration into the eye - Rabbit Standard Draize test: 750 ug/24H [Severe] (RTECS)

Skin Toxicity: Administration onto the skin - Rat LD50 - Lethal dose, 50 percent kill: >2150 mg/kg [Details of toxic effects not reported other than lethal dose value]

Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 2520 uL/kg [Details of toxic effects not reported other than lethal dose value](RTECS)

Ingestion Toxicity: Oral - Rat LD50 - Lethal dose, 50 percent kill: 1660 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Lungs, Thorax, or Respiration - Respiratory depression] (RTECS)

Inhalation Toxicity: Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: 1030 ppm/8H [Sense Organs and Special Senses (Eye) - Lacrimation Gastrointestinal - Changes in structure or function of salivary glands Lungs,

Thorax, or Respiration - Dyspnea] (RTECS)

Section 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Ecotoxicity: No ecotoxicity data was found for the product.

12.2 Persistence and degradability

Environmental Fate: No environmental information found for this product.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

Section 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste Disposal: Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws. Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

Do not reuse, heat, burn, pressurize, cut, weld, braze, solder, drill, grind, expose to sparks, flame, or ignition sources of empty containers without proper commercial cleaning or reconditioning.

Section 14. TRANSPORT INFORMATION

14.1 UN Number: UN3082

14.2 UN proper shipping name: Amines, liquid, corrosive, n.o.s.

14.3. Transport hazard class(es): 9

14.4 Packing group: III

14.5 Environmental hazards Environmentally hazardous substance, liquid, n.o.s.

14.6 Special precautions for user None.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

DOT Shipping Name: Amines, liquid, corrosive, n.o.s.

DOT UN Number: UN3082

DOT Shipping Name: Amines, liquid, corrosive, n.o.s.

DOT Hazard Class 9

DOT Packing Group: III

IMDG Shipping Name: Environmentally hazardous substance, liquid, n.o.s.

IMDG UN Number: UN3082

IMDG Hazard Class: 9

IMDG Packing Group:	III
IATA Shipping Name:	Environmentally hazardous substance, liquid, n.o.s.
IATA UN Number:	UN3082
IATA Hazard Class:	III
IATA Subrisk:	9
Notes from Section 14:	The data provided in this section is for information only. Please apply the appropriate regulations to properly classify your shipment. This classification applies only to transportation classification and not the packaging, labeling, or marking requirements. The shipper is responsible for complying with all applicable laws and regulations, including proper transportation classification, packaging, and labeling.

Section 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation: Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Regulatory - Ingredient Based:

N-butyl Glycidyl Ether:

Canada Listed

DSL:

TSCA Listed

Inventory Status:

EC 219-376-4

Number:

Bisphenol A/epichlorohydrin Resin:

Canada Listed

DSL:

TSCA Listed

Inventory Status:

EC 500-033-5

Number:

15.2 Chemical safety assessment

No data available.

Section 16. OTHER INFORMATION

Issue Date: July 13, 2018

Revision Date: July 13, 2018

HMIS:

Health	2
Flammability	1
Reactivity	1
PPE	X

NFPA

Safety Data Sheet**115-3302**

CircuitMedic, 22 Parkridge Road, Haverhill, MA 01835 USA
Phone: 978-373-1600 | Website: <http://www.circuitmedic.com>

Revision Date: Jul 13, 2018

CircuitMedic disclaims all liability associated with the use of this information.